

Hydrotech® Hydrocap 160FR

formerly known as Hydrocap 160FR



BUILDING TRUST



GENERAL DESCRIPTION

Hydrocap 160FR is a specially formulated, heavy duty, rubberized asphalt protection/cap sheet with polyester or a combination polyester and fiberglass reinforcement and a fire rated, non-combustible, ceramic granular surface.

BASIC USE

Hydrocap 160FR is specifically designed to be embedded into Hydrotech’s Monolithic Membrane 6125® roofing and waterproofing membrane assemblies to act as both protection for the membrane and the finished surface of the roof.

Additional protection is normally required in traffic areas and where physical abuse is anticipated.



SIZES

Hydrocap 160FR is available in roll form, with a width of 39.76 inches and a length of 33.5 feet. One roll equals approximately 110 square feet of material.

TECHNICAL DATA

PROPERTY	TEST METHOD	RESULTS
THICKNESS		0.160 in. (4.5mm) ± .003
WEIGHT		110 lbs (50kg)/roll
SOLAR REFLECTANCE	ASTM C1549	0.2735 (natural white)
SOLAR REFLECTANCE INDEX (SRI)	ASTM E1980	27
EMITTANCE	ASTM C1371	0.87 (natural white)

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	12 (pc), 56 (pi)	
Manufacture Location	Kansas City, MO	
Extraction/Harvesting Location	32% Chicago, IL	
VOC Content (g/L)	0	

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.