



Hydrotech[®] HydroSeal Catalyst

formerly known as HydroSeal Catalyst

GENERAL DESCRIPTION

HydroSeal Catalyst is a reactive agent in powder form.

BASIC USE

HydroSeal Catalyst is used as a reactive agent to initiate curing of HydroSeal methyl-methacrylate liquid resins and primers.

APPLICATION

Thoroughly mix the entire pail of resin for 2-3 minutes before pouring off into secondary container for batch mixing and adding Catalyst. Add premeasured Catalyst to the resin component and stir for 2 minutes using a slow-speed mechanical agitator or stirring stick.

The amount of catalyst added to HydroSeal Resins and Primers varies based on the resin type, quantity of resin to be used and temperature. Catalyze only the amount of material that can be used within the resins specified pot-life. Refer to individual resin product data sheets for specific recommendations and requirements for the resin or primer being used.

PACKAGING/SIZES/COVERAGE

HydroSeal Catalyst is supplied in pre-measured 2 and 5 kg pails as well as a carton of five 0.1 kg re-sealable packets.

PRECAUTIONS

Refer to product Safety Data Sheet (SDS) prior to use or handling.

The catalyst must only be stored in closed containers and in dry areas, away from heat and ignition sources and at temperatures below 77° F. In the original packaging it has a minimum shelf life of 12 months. The influence of heat can cause the powder to clump together and can reduce its effectiveness. The powder can self-ignite if it is heated to a higher temperature, e.g. by direct sunlight. Consequently, direct sunlight should also be avoided on site.

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.